



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: $> \phi 21.59\text{mm}$
2. SURFACE QUALITY: 10-5 SCRATCH-DIG
3. SURFACE FLATNESS: $< \lambda/10$ AT 633nm
4. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
5. THICKNESS TOLERANCE: $\pm 0.38\text{mm}$
6. COATING (ALL SURFACES): BBAR 350-700nm, $R_{\text{avg}} < 0.5\%$, 0° AOI
7. MINIMUM BEAM DIAMETER: 6mm

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 		THORLABS www.thorlabs.com	
	NAME	DATE	Ø 25.4mm QUARTZ DEPOLARIZER, -A COATED			
DRAWN	CFS	10/FEB/15				
APPROVAL	DD	17/FEB/15				
COPYRIGHT © 2015 BY THORLABS			MATERIAL		REV	
			LASER GRADE CRYSTAL QUARTZ		C	
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			ITEM #		APPROX WEIGHT	
			DPU-25-A		9.1 g	